WM190E

INDUSTRIAL WALL MOUNT LCD DISPLAY

Panel Type	19.0” TFT Active Matrix Panel
Max. Resolution	1280x1024 SXGA@75Hz
Pixel Pitch	0.294 (H) x 0.294 (V)
Contrast Ratio	900:1
Brightness	1,200 cd/m2
Back Light	LED
Display Area	376 x 301 mm
Response Time	5 ms (Typ.)
Display Colors	16.7 M
Viewing Angle	170 (H), 170 (V)
Signal Connector	RGB Analog 0.7V Peak to Peak
VGA Input Signal	15 Pin D-sub for VGA, RCA Video in, S-video
OSD Control	Power Switch, Menu, Select (+, -), Auto
Operation Temperature	0° ~ 50° C
Storage Temperature	-20° ~ 60° C
Power Consumption	40 W
Power Supply	External Power Adapter
Safely & EMI	CE, FCC, TUV-GS, UL Compliant
Front Bezel	Metal frame front cover
Mounting	Frame mount, VESA Mount (VESA 75/100)
LCD Protection	Option: Anti-Reflection Tempered Glass
Touch Screen	Option: Resistive/ Capacitive/ SAW; RS232/USB
Dimension	482 x 382 x 62 (mm) (not include OSD Keyboard) 18.98” x 15.04” x 2.64”
Net Weight	13.85 lbs (6.28 kg)

ACCUVIEW INC•
Tel: 800.275.4255 Fax: 201.440.5655 Address: 40C Cotters Lane, Suite F, East Brunswick, NJ 08816 Email: sales@accuview.com
*Specifications subject to change without notice. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 Accuview Inc. All rights reserved.